

## Between Series Adaptor 32\_BNC-SMB-50-2/1--\_U

### Description

Adaptor plug/plug  
BNC plug (male) / SMB plug (male)

Interface standards  
Series BNC - IEC 61169-8\_MIL-STD-348A/301\_CECC 22120  
Series SMB - IEC 60169-10\_MIL-STD-348A/311\_CECC 22130



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
Frequency range	DC to 4 GHz
Return loss	≥ 24 dB

#### Mechanical Data

Number of matings	500
Weight	0.0121 kg

#### Environmental Data

Operating temperature 2011/65/EC (RoHS)	-65 °C to 165 °C compliant
--	-------------------------------

#### Material Data

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - SMB plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Catalogue drawing	DCA-00014532
-------------------	--------------

### Ordering Information

Single package	32_BNC-SMB-50-2/1--_UE
----------------	------------------------