

## Coaxial Cable Connector 24\_BNT-50-3-1/103\_N

### Description

Straight bulkhead cable feed through

Interface standards  
SUHNER-BNT



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	3 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	clamped
Weight	0.0234 kg

#### Environmental Data

Operating temperature	-50 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00048069
Catalogue drawing	DCA-00009150
Assembly instruction	DOC-0000179264
Mounting hole	DOU-00008751

### Ordering Information

Single package	24_BNT-50-3-1/103_NE
----------------	----------------------

### Additional Information

Suitable cables	G_03332
-----------------	---------

### Remarks

Triaxial Connector