

## Between Series Adaptor 32\_N-PC35-50-1/1--\_U

### Description

Adaptor plug/plug  
N-precision plug (male) / PC 3.5 plug (male)

For Test & Measurement applications  
Precision adaptor

Interface standards  
Series N-precision - IEC 60169-16\_MIL-STD-348A/402\_CECC 22210  
Series PC 3.5 - IEC 60169-23



### Technical Data

#### Electrical Data

Impedance	50 Ω	
Interface frequency max.	18 GHz	
Frequency range	DC to 12.4 GHz	12.4 to 18 GHz
Return loss	≥ 26 dB	≥ 23 dB
Electrical length	41.5 mm	

#### Mechanical Data

Number of matings	500
Weight	0.0523 kg

#### Environmental Data

Operating temperature 2011/65/EC (RoHS)	-55 °C to 70 °C compliant
--	------------------------------

#### Material Data

Interface - N-precision plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - PC 3.5 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Bronze	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

### Related Documents

Catalogue drawing	DCA-00014506
-------------------	--------------

### Ordering Information

Single package	32_N-PC35-50-1/1--_UE
----------------	-----------------------

### Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C

## Between Series Adaptor 32\_N-PC35-50-1/1--\_U