

## Between Series Adaptor 33\_716-N-50-3/133\_W

### Description

PIM Adaptor plug/jack  
7/16 plug (male) / N jack (female)

Interface standards  
Series 7/16 - IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250  
Series N - IEC 61169-16\_MIL-STD-348A/304\_CECC 22210

#### Benefits

Low passive intermodulation (PIM) adaptor  
For Test & Measurement applications



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	7.5 GHz
PIM, 3rd order intermodulation distortion (IMD) max.	Static -165 dBc at 2x 43 dBm / 20 W carrier

#### Mechanical Data

Number of matings	500
Weight	0.0944 kg

#### Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-65 °C to 165 °C compliant
--	-------------------------------

#### Material Data

Interface - 7/16 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - N jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

### Related Documents

Outline drawing	DOU-00014415
-----------------	--------------

### Ordering Information

Single package	33_716-N-50-3/133_WE
----------------	----------------------