

## Coaxial Cable Connector 25\_716-50-5-17/000\_-

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$		
Interface frequency max.	7.5 GHz		
Frequency range	DC to 1 GHz	1 to 2.2 GHz	2.2 to 3.5 GHz
Return loss	40 dB	36 dB	27 dB

#### Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.1049 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PTFE (Polytetrafluoroethylene)	

### Related Documents

Outline drawing	DOU-00019498
Assembly instruction	DOC-0000215425

### Ordering Information

Tray package	25_716-50-5-17/000_-Y
--------------	-----------------------

### Additional Information

Suitable cables	SUCOFORM_250-01_FEP
-----------------	---------------------